



# IK-C2320E-P

2MP Hybrid HD Analogue Pinhole Camera

## Key Features

- 1/2.8" Progressive Scan CMOS
- 3.7mm pinhole lens
- Max 30fps@1080P
- Video transmission 300m
- 3D DNR, WDR, BLC, GLOBE, ATW
- Support AHD/TVI/CVI/CVBS Output

## Specification

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Signal System	PAL/NTSC
Electronic Shutter	Auto, PAL: 1/25 ~ 1/10000s, NTSC: 1/30 ~ 1/10000s
Min. illumination	Color: 0.001 Lux @ (F1.2, AGC ON), B/W: 0.0005 Lux @ (F1.2, AGC ON)
S/N Ratio	More than 50dB
OSD Joystick	Support
Up the Coax	Support
Lens	
Lens Type	Pinhole lens
Iris	Fixed Iris
Focal Length	3.7 mm
Max. Aperture	F2.0
Field of View (FoV)	H: 78°, V: 40.3°
Video	
Resolution	1080P (1920×1080)
Frame Rate	PAL: 25fps ,NTSC: 30fps
Video Output	Support AHD/TVI/CVI/CVBS Output
Day/Night	Auto / Color / B&W / EXT
OSD Menu	Support
Wide Dynamic Range	WDR, EXT/OPEN/CLOSE
Gain Control	Auto
Noise Reduction	3D DNR, AUTO/MANUAL (0-30)
White Balance	Auto
BLC	Support
General	
Power Supply	12 VDC ±10%

Power Consumption	Max. 2 W (12V DC, IR ON)
Operating Temperature	-10 °C to 55 °C (14°F to 131 °F)
Operating Humidity	Less than 85% RH
Ingress Protection	N/A
Certifications	CE-EMC: - EN 61000-6-3, EN 61000-3-2, EN 61000-3-3, EN 50130-4 FCC 47 CFR Part 15 Subpart B
Material	Metal
Dimensions	46.4 × 57 × 20 mm (Φ4.37 × 3.74 inch)
Net Weight	0.11 kg (0.73 lb)

## Dimensions (mm)

